



Manufactured by: HARPO spa – **Rialto** division 34123 Trieste - Italy
Tech. Sheet N°: 74/P/RI
Product name: **RIALTO FONDO DI ADERENZA 1 E 2**
Revision nr. 6 dated: 01.12.2008

01. IDENTIFICATION OF THE PREPARATION AND THE COMPANY

1.1 Identification of the substance or preparation:

Product name: Rialto Fondo di Aderenza 1 e 2.

1.2 Use of the substance/preparation:

Intended use: Rialto Fondo di Aderenza 1 e 2 is an ideal undercoat for finish made out of silicate and mineral compounds.

Chemical name and synonym: Products based on potassium silicate, sand and additives.

1.3 Company Identification:

Name: HARPO spa.

Full address: Via Torino, 34

District and Country: 34123 - Trieste, Italy,
tel. +39 040 3186611, fax +39 0403186666

E-mail address of the competent person responsible for the Safety Data Sheet: rialto@rialto-colors.com (rif. Dr. Renni – technical manager)

Product distribution by: Harpo spa

1.4 Telephone number for urgent inquiries: + 39 040 2397211 (timetable: 8.00 – 16.30)

02. HAZARD IDENTIFICATION

This preparate is not dangerous under 67/548/EEC and 1999/45/EC directives and subsequent amendments (Directive 2006/8/CE). Nevertheless, this preparate contains substances h a community workplace exposure limit that must be declared in section No. 3 and requires a safety data sheet containing all the information required under the Regulation (EC) 1907/2006 and subsequent amendments.

03. COMPOSITION/INFORMATION ON INGREDIENTS

Denominazione	Concentrazione (C)	Classificazione
Calcium and magnesium carbonate Cas No 16389-88-1 CE No 240-440-2 Substance with a community workplace exposure limit	9 – 11 %	-
MICA Cas No 12001-26-2 Substance with a community workplace exposure limit	1,0 – 1,5 %	-
Titanium dioxide Cas No 13463-67-7 CE No 236-675-5 Substance with a community workplace exposure limit	5 – 8 %	-
Quartz Cas No 14808-60-7 CE No 238-877-9 Substance with a community workplace exposure limit	7,0 – 9,0 %	Xn R48/20
Chlorite Cas No 1318-59-8 CE No 215-285-9 Substance with a community workplace exposure limit	1,0 – 1,5 %	-

The complete text of – R – phrases is specified in section 16.

04. FIRST – AID MEASURES

EYES: Irrigate copiously with clean, fresh water for at least 15 minutes. Seek medical advice.

Manufactured by: HARPO spa – **Rialto** division 34123 Trieste - Italy
Tech. Sheet N°: 74/P/RI
Product name: **RIALTO FONDO DI ADERENZA 1 E 2**
Revision nr. 6 dated: 01.12.2008

SKIN: Wash immediately with plenty of water. Remove contaminated clothing. If irritation persists seek medical attention. Wash contaminated clothing before using them.

INHALATION: Remove to fresh air. If breathing is irregular seek medical advice.

INGESTION: Obtain immediate medical attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person.



In all cases of doubt or if symptoms persist, resorting to medical care.
Never give anything by mouth, if the person is unconscious.

05. FIRE – FIGHTING MEASURES

Allow containers to cool in order to avoid product decomposition and generation of substances which might injure the health and be dangerous for safety reasons. Wear the fire equipment all the time.

06. ACCIDENTAL RELEASE MEASURES

Collect the largest amount of the solid product with mechanical tools. Avoid the formation of dust spraying the product with moist cleansing agents or water.

06. HANDLING AND STORAGE

Store in a wellventilated place keeping the containers closed when not used. Do not smoke while handling. Keep far away from sources of heat, naked flames and sparks and other sources of ignition; do not spray in the vicinity of flames or incandescent materials

08. EXPOSURE CONTROLS/PERSONAL PROTECTION

Calcium, magnesium carbonate			
- TLV TWA	10	mg/m ³	ACGIH
Mica			
- TLV TWA	0,1	mg/m ³	ACGIH
Chlorite			
- TLV TWA	0,1	mg/m ³	ACGIH
Quartz			
- TLV TWA	0,1	mg/m ³	ACGIH
Titanium dioxide			
- TLV TWA	10	mg/m ³	ACGIH

- The data refer to the substances and not to the mixture.

Adopt the closed circuit, if possible. If lacking, in order to avoid exposure and prevent its possible effects, even longterm, it is necessary to use adequate individual protective measures such as: masks, safety goggles, impermeable gloves and overalls, resistant to the product. Ensure that all the operators follow the recommended precautions. Attach a copy to the containers in which the product may be transferred and do not use the product if the working conditions do not correspond to the recommended precautions; avoid contact with the eyes and skin and prolonged breathing of the vapours; store the container sealed when not being used. Do not eat, drink or smoke while handling it. Accurately wash the hands with soap and water before meals and take a shower at the end of the work shift. Working clothes should be washed separately and stored in a separate place. In order to prevent longterm effects, periodic health controls should be carried out even if not established by the Law, including supplementary examinations which are deemed necessary according to the discretion of the occupational physician.

09. PHYSICAL AND CHEMICAL PROPERTIES

Odour Slight of ammonia



Manufactured by: HARPO spa – **Rialto** division 34123 Trieste - Italy
Tech. Sheet N°: 74/P/RI
Product name: **RIALTO FONDO DI ADERENZA 1 E 2**
Revision nr. 6 dated: 01.12.2008

Colour	White
Physical appearance	Opaque sand
Solubility in solvents	Partially miscible
Solubility in water	Miscible
Volatile substances % by volume (solvents)	1,6 % max
Hazardous reactions	N/A
Viscosity	9000 ± 1000 mPas
Vapour density	> 1
Evaporation speed	N/A
Comburent properties	N.A.
Partition coefficient: n-octanol/water	N.A.
pH	12,50 ± 0,5
Boiling point	> 150 °C
Flash point	N.A.
Explosive properties	N.A.
Vapour pressure	N.D.
Specific gravity	1,53 - 0,01 Kg/l
VOC (Directive 2004/42/EC):	< 2 % - 20 g/l
VOC (volatile carbon):	< 1 % - 14,36 g/l

10. STABILITY AND REACTIVITY

The product is stable in normal conditions of use and storage. In the event of thermal decomposition or fire, vapours potentially dangerous to health may be released. Propylene glycol: it is hygroscopic, stable at normal conditions; at high temperatures, it tends to oxidize yielding propionaldehyde as well as lactic and acetic acid. Calcium carbonate: avoid contact with acids.

11. TOXICOLOGICAL INFORMATION

According to currently available data, this product has not yet produced health damages. Anyway, it must be handled carefully according to good industrial practices. This preparate may have slight health effects on sensitive people, by inhalation and/or cutaneous absorption and/or contact with eyes and/or ingestion.

CALCIUM CARBONATE: oral LD50 (mg/kg) 6450 (RAT)

TITANIUM DIOXIDE: oral LD50 (mg/kg) > 10000 (RAT)

1,2-PROPANEDIOL: oral LD50 (mg/kg) 20800 (RAT) ; dermal LD50 (mg/kg) 20800 (RAT)

12. ECOLOGICAL INFORMATION

Use this product according to good working practices. Avoid litter. Inform the competent authorities, should the product reach waterways or sewers or contaminate soil or vegetation.

13. DISPOSAL CONSIDERATIONS

Consider the possibility of burning the product in a suitable incenerator. Acid or basic products must always be neutralized before undergoing any treatment, including biological treatment whenever feasible. If the waste is solid, it can be disposed of in a landfill.

14. TRANSPORT INFORMATIONS

This substance is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

15. REGULATORY INFORMATION

Warning symbols: None

Hazard sentences (R): None

Caution recommendations (S): None



Manufactured by: HARPO spa – **Rialto** division 34123 Trieste - Italy
Tech. Sheet N°: 74/P/RI
Product name: **RIALTO FONDO DI ADERENZA 1 E 2**
Revision nr. 6 dated: 01.12.2008

This product is not subject to hazard labeling under the 67/548/EEC and 1999/45/EC directives and following amendments and adjustments (directive 2006/8/EC and regulation 1907/EC).

DIRECTIVE 2004/42/EC

Paint for exterior walls of mineral substrate (WB)

EU limit value for this product (**A/c**): 75 g/l (2007); 40 g/l (2010)

This product contains at maximum: **30 g/l** of VOC

16. FURTHER INFORMATIONS

Text of – R – phrases quoted in section 3 of the sheet.

R48/20

HARMFUL: DANGER OF SERIOUS DAMAGE TO HEALTH BY
REPEATED EXPOSURE BY INHALATION.

GENERAL BIBLIOGRAPHY

1. Regulation 2006/8/CE
2. Regulation 1999/45/CE and following amendments (technical adjustment XXX);
3. Regulation 67/548/CEE and following amendments and adjustments (technical adjustment XXVIII);
4. Regulation 91/155/CEE and following amendments;
5. Regulation (EC) 1907/2006 and subsequent amendments.
6. The Merck Index. - 10th Edition;
7. Handling Chemical Safety;
8. Niosh - Registry of Toxic Effects of Chemical Substances;
9. INRS - Fiche Toxicologique (toxicological sheet);
10. Patty - Industrial Hygiene and Toxicology;
11. N.I. Sax-Dangerous properties of Industrial Materials-7, 1989 Edition;

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product. This document must not be regarded as a guarantee on any specific product property. The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Changes to previous review
The following sections were modified:
01/ 02 / 03 / 08 / 11 / 15 / 16