Manufactured by: Tech. Sheet N°. Product name: Revision nr. 5 dated: - according to european directive 2006/8/EC and to regulation (EC) N. 1907/2006

HARPO spa – **Rialto** division 34123 Trieste - Italy 10A/F/RI **RIALTO MARINA** 01.10.2008



### 01. IDENTIFICATION OF THE PREPARATION AND THE COMPANY/

reparation:
Rialto Eralit.
Fine grain coating for interiors and exteriors.
Copolymer resin, selected colored fine grain marble chippings, pigments resistant to UV rays.
HARPO spa.
Via Torino, 34
34123 - Trieste, Italy, tel. +39 040 3186611, fax +39 0403186666
rialto@rialto-colors.com (rif. Dr. Renni – technical manager)
Harpo spa
+ 39 040 2397211 (timetable: 8.00 – 16.30)

#### 02. HAZARD IDENTIFICATION

Containa

This compound is not dangerous under 67/548/EEC and 1999/45/EC directives and subsequent amendments (Directive 2006/8/CE). Nevertheless, this compound contains substances in concentrations that must be declared in section No. 3 and requires a safety data sheet containing all the information required under the Regulation (EC) 1907/2006 and subsequent amendments.

#### 03. COMPOSITION/INFORMATION ON INGREDIENTS

Contains: Name	Concentration C	Classification
Calcium and magnesium carbonate	25 – 30 %	-
Cas No 16389-88-1		
CE No 240-440-2	ovpoquro limit	
Substance with a community workplace	1	
Calcium carbonate	38 – 42 %	-
Cas No 471-34-1		
CE No 207-439-9		
Substance with a community workplace	exposure limit	
Titanium dioxide	2 – 5 %	-
Cas No 13463-67-7		
CE No 236-675-5		
Substance with a community workplace	exposure limit	
5-CHLORO-2METHYL-2H-		
ISOTHIAZOL-3-ONE/2-METHYL-2H-	0 - 0,0005 %	T, R23/24/25
ISOTHIAZOL-3-ONE (3:1) Cas No 55965-84-9		
Index No 613-167-00-5		C, R34
		Xi, R43
		N, R50/53
Propylene glycol	1 – 5 %	
Cas No 57-55-6		
CE No 200-338-0		

Substance with a community workplace exposure limit

Manufactured by: Tech. Sheet N°. Product name: Revision nr. 5 dated: according to european directive 2006/8/EC and to regulation (EC) N. 1907/2006

HARPO spa – **Rialto** division 34123 Trieste - Italy 10A/F/RI **RIALTO MARINA** 01.10.2008



### 04. FIRST – AID MEASURES

**EYES:** Irrigate copiously with clean, fresh water for at least 15 minutes. Seek medical advice. **SKIN:** Wash immediately with plenty of water. Remove contaminated clothing. If irritation persists seek medical attention. Wash contaminated clothing before using them.

**INHALATION:** Remove to fresh air. If breathing is irregular seek medical advice.

**INGESTION:** Obtain immediate medical attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person.

#### 05. FIRE - FIGHTING MEASURES

Allow containers to cool in order to avoid product decomposition and generation of substances which might injure the health and be dangerous for safety reasons. Wear the fire equipment all the time.

# 06. ACCIDENTAL RELEASE MEASURES

Extinguish the sources of ignition or heat; cover the spillage with inert absorbent material. Collect as far apossible the resulting mass and discard the remainder by spraying water, if not contraindicated. For information on environmental and health risks, protection of the respiratory airways, ventilation and individual protective measures refer to the other sections of this sheet.

### 07. HANDLING AND STORAGE

Make sure that equipment is available for cooling the vessels, to prevent the danger of overpressure and overheating in the event of fire in the vicinity. Refer to the other sections of this data sheet for information relating to health and environmental risks.

#### 08. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Exposure limit values:			
Calcium carbonate/			
Calcium, magnesium carbonate			
- TLV TWA	10	mg/m <sup>3</sup>	ACGIH
Titanium dioxide			
- TLV TWA	10	mg/m <sup>3</sup>	ACGIH
Propylen glicol			
TLV OEL (IRL)	10	mg/m <sup>3</sup>	TWA/8h
TLV RV (LT)	7	mg/m <sup>3</sup>	TWA/8h
TLV WEL (ÚK)	150	mg/m <sup>3</sup>	TWA/8h
The data refer to the substance	es and not to the mix		

• The data refer to the substances and not to the mixture.

#### 8.2 Exposure controls:

Adopt the closed circuit, if possible. If lacking, in order to avoid exposure and prevent its possible effects, even long-term, it is necessary to use adequate individual protective measures such as: masks, safety goggles, impermeable gloves and overalls, resistant to the product:



Ensure that all the operators follow the recommended precautions. Attach a copy to the containers in which the product may be transferred and do not use the product if the working conditions do not correspond to the recommended precautions; avoid contact with the eyes and skin and prolonged breathing of the vapours; store the container sealed when not being used. Do not eat, drink or smoke while handling it. Accurately wash the hands with soap and water before meals and take a shower at the end of the work shift. Working clothes should be washed separately and stored in a separate place. In order to prevent long-term effects, periodic health controls should be carried out even if not established by the Law, including supplementary examinations which are deemed necessary according to the discretion of the occupational physician.

Manufactured by: Tech. Sheet N<sup>a</sup>. Product name: Revision nr. 5 dated: according to european directive 2006/8/EC and to regulation (EC) N. 1907/2006

HARPO spa – **Rialto** division 34123 Trieste - Italy 10A/F/RI **RIALTO MARINA** 01.10.2008



### 09. PHYSICAL AND CHEMICAL PROPERTIES

Odour Physical appearance Solubility in solvents Solubility in water	Slight Coloured paste Partially miscible Miscible
Volatile substances % by volume (solvents)	1%
Hazardous reactions Viscosity Vapour density Evaporation speed	N/A 18.000 ± 2.000 mPas 1 < 1
Comburent properties Partition coefficient: n-	N.D.
octanol/water	N.D.
pH Roiling point	8,40 ± 0,20 > 150 °C
Boiling point Flash point	N.D.
Explosive properties	N.D.
Vapour pressure Specific gravity	N.D. 1,60 ± 0,20 Kg/l
Solid content (by weight)	81,00 ± 2,00 %
VOC (Directive 2004/42/EC):	<4% - 38 g/l
VOC (volatile carbon)	<2% - 28 g/l

#### 10. STABILITY AND REACTIVITY

The product is stable in normal conditions of use and storage. In the event of thermal decomposition or fire, vapours potentially dangerous to health may be released.

# 11. TOXICOLOGICAL INFORMATION

According to currently available data, this product has not yet produced health damages. Anyway, it must be handled carefully according to good industrial practices. This preparate may have slight health effects on sensitive people, by inhalation and/or cutaneous absorption and/or contact with eyes and/or ingestion.

CALCIUM CARBONATE: oral LD50 (mg/kg) 6450 (RAT) TITANIUM DIOXIDE: oral LD50 (mg/kg) > 10000 (RAT) 1,2-PROPANEDIOL: oral LD50 (mg/kg) 20800 (RAT) ; dermal LD50 (mg/kg) 20800 (RAT)

#### 12. ECOLOGICAL INFORMATION

Use this product according to good working practices. Avoid litter. Inform the competent authorities, should the product reach waterways or sewers or contaminate soil or vegetation.

 MIT / CIT (3:1)

 EC50 (48h):
 0,12 mg/l DAPHNIA MAGNA

 LC50 (96h):
 0,22 mg/l Oncorhynchus mykiss

#### 13. DISPOSAL CONSIDERATIONS

Consider the possibility of burning the product in a suitable inceneritor. Acid or basic products must always be neutralized before undergoing any treatment, including biological treatment whenever feasible. If the waste is solid, it can be disposed of in a landfill.

Manufactured by: Tech. Sheet N<sup>a</sup>. Product name: Revision nr. 5 dated: according to european directive 2006/8/EC and to regulation (EC) N. 1907/2006

HARPO spa – **Rialto** division 34123 Trieste - Italy 10A/F/RI **RIALTO MARINA** 01.10.2008



### 14. TRANSPORT INFORMATIONS

This substance is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

#### 15. REGULATORY INFORMATION

Warning symbols: None Hazard sentences (R): None Caution recommendations (S): None

This product is not subject to hazard labeling under the 67/548/EEC and 1999/45/EC directives and following amendments and adjustments (directive 2006/8/EC and regulation n. 1907/EC).

#### DIRECTIVE 2004/42/EC

## Paint for exterior walls of mineral substrate (WB)

EU limit value for this product (**A/c**): 75 g/l (2007); 40 g/l (2010) This product contains at maximum: **38 g/l** of VOC

#### 16. FURTHER INFORMATIONS

Text of -R- phrases quoted in section 3 of the sheet.

R23/24/25	Toxic by inhalation, in contact with skin and if swallowed.
R34	Causes burns.
R43	May cause sensitization by skin contact.
R50/53	Very toxic to aquatic organism, may cause long term adverse effect
	to the aquatic environment.

#### GENERAL BIBLIOGRAPHY

- 1. Regulation 2006/8/CE
- 2. Regulation 1999/45/CE and following amendments (technical adjustment XXX);
- 3. Regulation 67/548/CEE and following amendments and adjustments (technical adjustment XXVIII);
- 4. Regulation 91/155/CEE and following amendments;
- 5. Regulation (EC) 1907/2006 and subsequent amendments.
- 6. The Merck Index. 10th Edition;
- 7. Handling Chemical Safety;
- 8. Niosh Registry of Toxic Effects of Chemical Substances;
- 9. INRS Fiche Toxicologique (toxicological sheet);
- 10. Patty Industrial Hygiene and Toxicology;
- 11. N.I. Sax-Dangerous properties of Industrial Materials-7, 1989 Edition;
  - Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product. This document must not de regarded as a guarantee on any specific product property. The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Changes to previous review The following sections were modified: 01/ 02 / 03 / 08 / 09 / 11 / 15 / 16