Manufactured by: HARPO spa - Rialto division 34123 Trieste

Tech. Sheet N°. 49B/F/RI

Product name: RIALTO ROLLER SILOSSANICO

Revision nr. 4 dated: 25.06.2008



01. IDENTIFICATION OF THE PREPARATION AND THE COMPANY

1.1 Identification of the substance or preparation:

Product name: Rialto Roller Silossanico.

1.2 Use of the substance/preparation:

Intended use: Siloxane based finishing coating ideal to give a high decorative

"orange peel" effect to walls..

Chemical name and synonym: Siloxane resin, colored fine grain marble chippings, hard

aggregates including granite and quartz, pigments UV resistant.

Ola - - ifi - - - i - - -

1.3 Company Identification:

Name: HARPO spa.
Full address: Via Torino, 34

District and Country: 34123 - Trieste, Italy,

tel. +39 040 3186611, fax +39 0403186666

E-mail address of the competent

person responsible for the Safety rialto@rialto-colors.com (rif. Dr. Renni – technical manager)

Data Sheet:

Product distribution by: Harpo spa

1.4 Telephone number for urgent

+ 39 040 2397211 (timetable: 8.00 – 16.30)

02. HAZARD IDENTIFICATION

Substance/Preparation Classification.

This preparation is dangerous under 67/548/EEC and 1999/45/EC regulations and subsequent amendments (XXX ATP). This compound requires a safety data sheet according to the regulation 1907/2006 and the directive 2006/8/EC and subsequent amendments. Further information on health and/or environmental hazards can be found in sections 11 and 12 of this sheet.

Danger Symbol: Xn

Phrases R: 43 - 48/20 - 52/53

Danger identification.

May cause sensitisation by skin contact.

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

03. COMPOSITION/INFORMATION ON INGREDIENTS

Denominazione	Concentrazione (C)	Classificazione
5-chloro-2-methyl-2H-isothiazol-3-one /2-methyl-2H-isothiazol-3-one (3:1)	0,0002 - 0,0004%	T R23/24/25
N°Cas 55965-84-9		C R 34
N°Index 613-167-00-5		Xi R 43
		N R 50/53
Quartz	63,00 - 66,00 %	Xn R48/20
Cas No 14808-60-7		
CE No 238-878-4		
Propylene glycol	0,00 – 1,00 %	
Cas No 57-55-6		
CE No 200-338-0		
Substance with a community workplace	exposure limit	

The complete text of -R – phrases is specified in section 16.

Manufactured by: HARPO spa - Rialto division 34123 Trieste

Tech. Sheet N°. 49B/F/RI

Product name: RIALTO ROLLER SILOSSANICO

Revision nr. 4 dated: 25.06.2008




04. FIRST - AID MEASURES

EYES: Irrigate copiously with clean, fresh water for at least 15 minutes. Seek medical advice.

SKIN: Wash immediately with plenty of water. Remove contaminated clothing. If irritation persists seek medical attention. Wash contaminated clothing before using them.

INHALATION: Remove to fresh air. If breathing is irregular seek medical advice.

INGESTION: Obtain immediate medical attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person.



In all cases of doubt or if symptoms persist, seek medical advice. Never give anything by mouth to an unconscious person.

05. FIRE - FIGHTING MEASURES

Allow containers to cool in order to avoid product decomposition and generation of substances which might injure the health and be dangerous for safety reasons. Wear the fire equipment all the time.

06. ACCIDENTAL RELEASE MEASURES

Collect the largest amount of the solid product with mechanical tools. Avoid the formation of dust spraying the product with moist cleansing agents or water

07. HANDLING AND STORAGE

Make sure that equipment is available for cooling the vessels, to prevent the danger of overpressure and overheating in the event of fire in the vicinity. Refer to the other sections of this data sheet for information relating to health and environmental risks.

08. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Exposure limit values:

Calcium carbonate mg/m³ - TLV TWA 10 **ACGIH** Quartz - TLV TWA mg/m³ **ACGIH** 0,05 Glicole propilenico mg/m³ - TLV OEL (IRL) 10 TWA/8h mg/m³ - TLV RV (LT) TWA/8h mg/m³ - TLV WEL (IUK) 150 TWA/8h

8.2 Exposure controls:

Follow the good industrial hygiene practices adopting suitable individual protective measures such as masks, safety goggles, impermeable gloves and overalls:



Do not eat or smoke while handling the product. Wash hands before eating and at the end of the work shift. Periodic health controls are recommended at the discretion of the doctor.

Manufactured by: HARPO spa - Rialto division 34123 Trieste

Tech. Sheet N°. 49B/F/RI

Product name: RIALTO ROLLER SILOSSANICO

Revision nr. 4 dated: 25.06.2008



09. PHYSICAL AND CHEMICAL PROPERTIES

Odour Slight

Physical appearance Coloured paste Solubility in solvents Partially miscible

Solubility in water Miscible

Volatile substances % by volume (solvents)

Hazardous reactions

1%

Viscosity $18.500 \pm 500 \text{ mPas}$

Vapour density 1
Evaporation speed < 1
Comburent properties N/A
Partition coefficient: noctanol/water N.D.

pH $7,50 \pm 0,20$ Boiling point > 150 ℃ Flash point N.A. Explosive properties N.A. Vapour pressure N.D.

Specific gravity 1,70 \pm 0,1 Kg/l Solid content (by weight): 75,00 \pm 0,50% VOC (directive 2004/42/CE) < 1,00 % - 13 g/l < 1,00 % - 8 g/l

10. STABILITY AND REACTIVITY

The product is stable in normal conditions of use and storage. In the event of thermal decomposition or fire, vapours potentially dangerous to health may be released.

11. INFORMAZIONI TOSSICOLOGICHE

Upon contact with skin, this product causes sensitization (dermatitis). Dermatitis derives from skin irritation on the areas which repeatedly come into contact with the sensitizing agent. Cutaneous lesions may include: erythemas, edemas, papules, vescicles, pustules, scurves, ulcerations and exudative phenomena, whose intensity varies according to illness seriousness and affected areas. Erythemas, edemas and exudative phenomena prevail during the acute phase. Scurfy skin, dryness, ulcerations and skin thickening prevail during the chronic phase. This product may cause functional disorders or morphological mutations after repeated or prolonged exposure by inhalation of a quantity of 0.25 mg/l/6h/day or lower.

CALCIUM AND MAGNESIUM CARBONATE: LD50 oral (mg/kg) 6450 (rat) PROPYLENE GLYCOL: LD50 oral (mg/kg) 20800 (rat), dermal LD50 (mg/kg) 20800 (rat)

12. ECOLOGICAL INFORMATION

Use this product according to good working practices. Avoid litter. Inform the competent authorities, should the product reach waterways or sewers or contaminate soil or vegetation.

13. DISPOSAL CONSIDERATIONS

Consider the possibility of burning the product in a suitable inceneritor. Acid or basic products must always be neutralized before undergoing any treatment, including biological treatment whenever feasible. If the waste is solid, it can be disposed of in a landfill.

Manufactured by: HARPO spa - Rialto division 34123 Trieste

Tech. Sheet N°. 49B/F/RI

Product name: RIALTO ROLLER SILOSSANICO

Revision nr. 4 dated: 25.06.2008



14. TRANSPORT INFORMATIONS

This substance is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

15. REGULATORY INFORMATION



R43 MAY CAUSE SENSITIIZATION BY SKIN CONTACT.

R48/20 HARMFUL: DANGER OF SERIOUS DAMAGE TO HEALTH BY PROLONGED EXPOSURE

THROUGH INHALATION.

R52/53 HARMFUL TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECT IN THE

AQUATIC ENVIRONMENT.

S2 KEEP OUT OF REACH OF CHILDREN.

S 9 KEEP CONTAINER IN A WELL-VENTILATED PLACE.

S13 KEEP AWAY FROM FOOD, DRINK AND ANIMAL FEEDINGSTUFFS.

S22 DO NOT BREATHE DUST S24 AVOID CONTACT WITH SKIN.

S37 IN CASE OF INSUFFICIENT VENTILATION, WEAR SUITABLE RESPIRATORY EQUIPMENT.

S38 WEAR SUITABLE GLOVES.

Contains:

Crystalline silica, terbutryn and 5-chloro-2-methyl-2H-isothiazol-3-one/2-methyl-2H-isothiazol-3-one (3:1)

Danger labelling under regulations 67/548/CEE and 1999/45/CE and following amendments and adjustments (XXX ATP).

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/CE regulation is respected.

DIRECTIVE 2004/42/EC

Paint for exterior walls of mineral substrate (WB)

EU limit value for this product (**A/c**): 75 g/l (2007); 40 g/l (2010)

This product contains at maximum: 38 g/l of VOC

16. FURTHER INFORMATIONS

Text of -R- phrases quoted in section 3 of the sheet.

R23/24/25 $\,$ TOXIC BY INHALATION, IN CONTACT WITH SKIN AND IF SWALLOWED.

R34 CAUSES BURNS

R43 MAY CAUSE SENSITIIZATION BY SKIN CONTACT.

HARMFUL: DANGER OF SERIOUS DAMAGE TO HEALTH BY PROLONGED EXPOSURE

R48/20 THROUGH INHALATION.

R50/53 VERY TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECT IN THE

AQUATIC ENVIRONMENT

GENERAL BIBLIOGRAPHY

- 1. Regulation 1999/45/CE and following amendments (directive 2006/8/CE);
- 2. Regulation 67/548/CEE and following amendments and adjustments (technical adjustment XXVIII);
- 3. Regulation n. 1907/EC.

Manufactured by: HARPO spa - Rialto division 34123 Trieste

Tech. Sheet N°. 49B/F/RI

Product name: RIALTO ROLLER SILOSSANICO

Revision nr. 4 dated: 25.06.2008



- 4. Regulation 91/155/CEE and following amendments;
- 5. The Merck Index. 10th Edition;
- 6. Handling Chemical Safety;
- 7. Niosh Registry of Toxic Effects of Chemical Substances;
- 8. INRS Fiche Toxicologique (toxicological sheet);
- 9. Patty Industrial Hygiene and Toxicology;
- 10. N.I. Sax-Dangerous properties of Industrial Materials-7, 1989 Edition;

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product. This document must not de regarded as a guarantee on any specific product property. The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Changes to previous review
The following sections were modified:
01/ 02 / 03 / 04 / 08 / 09 / 10 / 11 / 15 / 16