



Manufactured by:  
Tech. Sheet N°:  
Product name:  
Revision nr. 6 dated:

HARPO spa – **Rialto** division 34123 Trieste - Italy  
52/P/RI  
**RIALTO WHITY**  
01.11.08

## 01. IDENTIFICATION OF THE PREPARATION AND THE COMPANY

### 1.1 Identification of the substance or preparation:

**Product name:** Rialto Whity.

### 1.2 Use of the substance/preparation:

**Intended use:** This siloxane product provides a smooth and opaque veiled effect for interiors and exteriors.

**Chemical name and synonym:** Water veiled finish made out of modified siloxane resin, sands and pigments.

### 1.3 Company Identification:

**Name:** HARPO spa.

**Full address:** Via Torino, 34

34123 - Trieste, Italy,

**District and Country:** tel. +39 040 3186611, fax +39 0403186666

**E-mail address of the competent person responsible for the Safety Data Sheet:** rialto@rialto-colors.com (rif. Dr. Renzi – technical manager)

**Product distribution by:** Harpo spa

**1.4 Telephone number for urgent inquiries:** + 39 040 2397211 (timetable: 8.00 – 16.30)

## 02. HAZARD IDENTIFICATION

### Substance/Preparation Classification.

This preparation is dangerous under 67/548/EEC and 1999/45/EC regulations and subsequent amendments (XXX ATP). This compound requires a safety data sheet according to the regulation 1907/2006 and the directive 2006/8/EC and subsequent amendments. Further information on health and/or environmental hazards can be found in sections 11 and 12 of this sheet.

**Danger Symbol:** -

**Phrases R:** 52/53

### Danger identification.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

## 03. COMPOSITION/INFORMATION ON INGREDIENTS

Name	Concentration (C)	Classification
Calcium and magnesium carbonate N°Cas 16389-88-1 N°CE 240-440-2 Substance with a community workplace exposure limit	8 – 10 %	-
CALCIUM CARBONATE Cas No 471-34-1 CE No 207-439-9 Substance with a community workplace exposure limit	18 – 19 %	-
5-chloro-2-methyl-2H-isothiazol-3-one /2-methyl-2H-isothiazol-3-one (3 :1) N°Cas 55965-84-9 N°Index 613-167-00-5	0,0010 – 0,0014%	T R23/24/25 C R 34 Xi R 43 N R 50/53
Titanium dioxide Cas No 13463-67-7 CE No 236-675-5 Substance with a community workplace exposure limit	8,0 – 10 %	-

Manufactured by:  
Tech. Sheet N°:  
Product name:  
Revision nr. 6 dated:

HARPO spa – **Rialto** division 34123 Trieste - Italy  
52/P/RI  
**RIALTO WHITY**  
01.11.08

Talc 8,0 – 10 % -  
Cas No 14807-96-6  
CE No 238-877-9  
Substance with a community workplace exposure limit  
The complete text of – R – phrases is specified in section 16.

#### 04. **FIRST – AID MEASURES**

**EYES:** Irrigate copiously with clean, fresh water for at least 15 minutes. Seek medical advice.  
**SKIN:** Wash immediately with plenty of water. Remove contaminated clothing. If irritation persists seek medical attention. Wash contaminated clothing before using them.  
**INHALATION:** Remove to fresh air. If breathing is irregular seek medical advice.  
**INGESTION:** Obtain immediate medical attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person.



In all cases of doubt or if symptoms persist, resorting to medical care.  
Never give anything by mouth, if the person is unconscious.

#### 05. **FIRE – FIGHTING MEASURES**

Allow containers to cool in order to avoid product decomposition and generation of substances which might injure the health and be dangerous for safety reasons. Wear the fire equipment all the time.

#### 06. **ACCIDENTAL RELEASE MEASURES**

Collect the largest amount of the solid product with mechanical tools. Avoid the formation of dust spraying the product with moist cleansing agents or water.

#### 07. **HANDLING AND STORAGE**

Make sure that equipment is available for cooling the vessels, to prevent the danger of overpressure and overheating in the event of fire in the vicinity. Refer to the other sections of this data sheet for information relating to health and environmental risks.

#### 08. **EXPOSURE CONTROLS/PERSONAL PROTECTION**

Calcium, magnesium carbonate			
- TLV TWA	10	mg/m <sup>3</sup>	ACGIH
Talc			
- TLV TWA	2	mg/m <sup>3</sup>	ACGIH
Titanium dioxide			
- TLV TWA	10	mg/m <sup>3</sup>	ACGIH
Calcium carbonate			
- TLV TWA	10	mg/m <sup>3</sup>	ACGIH
Propylene glycol			
- TLV OEL	10	mg/m <sup>3</sup>	ACGIH
- TLV RV	7	mg/m <sup>3</sup>	ACGIH
- TLV WEL	150	mg/m <sup>3</sup>	ACGIH

- The data refer to the substances and not to the mixture.

In order to minimize exposure as far as possible, it is strongly recommended to use adequate individual protective measure such as: masks suitable for the product, goggles, gloves and overalls. Do not eat, drink or smoke while handling it. Accurately wash the hands with soap and water before meals and at the end of the end of the work shift.



Manufactured by:  
Tech. Sheet N°:  
Product name:  
Revision nr. 6 dated:

HARPO spa – **Rialto** division 34123 Trieste - Italy  
52/P/RI  
**RIALTO WHITY**  
01.11.08

## **09. PHYSICAL AND CHEMICAL PROPERTIES**

Odour	Slight
Physical appearance	Creamy
Solubility in solvents	Partially miscible
Solubility in water	Miscible
Volatile substances % by volume (solvents)	1 %
Hazardous reactions	N/A
Viscosity	c.a. 11.200 mPas
Vapour density	1
Evaporation speed	< 1
Comburent properties	N.A.
Partition coefficient: n-octanol/water	N.A.
pH	8,00 ± 0,20
Boiling point	> 150 °C
Flash point	N.A.
Explosive properties	N.A.
Vapour pressure	N.A.
Specific gravity	1,500 ± 0,05 Kg/l
Solid content (by weight)	66,00 ± 0,50 %
VOC (Directive 2004/42/EC):	< 2 % - 19 g/l
VOC (volatile carbon):	< 1 % - 10 g/l

## **10. STABILITY AND REACTIVITY**

The product is stable in normal conditions of use and storage. In the event of thermal decomposition or fire, vapours potentially dangerous to health may be released.

Propylene glycol: it is hygroscopic, stable at normal conditions; at high temperatures, it tends to oxidize yielding propionaldehyde as well as lactic and acetic acid. Calcium carbonate: avoid contact with acids.

## **11. TOXICOLOGICAL INFORMATION**

According to currently available data, this product has not yet produced health damages. Anyway, it must be handled carefully according to good industrial practices. This compound may have slight health effects on sensitive people, by inhalation and/or cutaneous absorption and/or contact with eyes and/or ingestion.

PROPYLEN GLYCOL: oral LD50 (mg/kg) 20800 (RAT) ; dermal LD50 (mg/kg) 20800 (RAT)

## **12. ECOLOGICAL INFORMATION**

Use this product according to good working practices. Avoid litter. Inform the competent authorities, should the product reach waterways or sewers or contaminate soil or vegetation.

## **13. DISPOSAL CONSIDERATIONS**

Consider the possibility of burning the product in a suitable incinerator. Acid or basic products must always be neutralized before undergoing any treatment, including biological treatment whenever feasible. If the waste is solid, it can be disposed of in a landfill.

## **14. TRANSPORT INFORMATIONS**

This substance is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA/ICAO).

## **15. REGULATORY INFORMATION**

Warning symbols: None



Manufactured by:  
Tech. Sheet N°:  
Product name:  
Revision nr. 6 dated:

HARPO spa – **Rialto** division 34123 Trieste - Italy  
52/P/RI  
**RIALTO WHITY**  
01.11.08

Hazard sentences (R): R52/53 – Harmful to aquatic organisms, may cause long-term adverse effect in the aquatic environment.

Caution recommendations (S): None

This product is not subject to hazard labelling under the 67/548/EEC and 1999/45/EC directives and following amendments and adjustments (directive 2006/8/EC).

**DIRECTIVE 2004/42/EC**

**Paints for interior matt walls and ceilings (WB) (gloss  $\leq$  25@60°)**

EU limit value (A/a): 75 g/l (2007); 30 g/l (2010)

This product contains at maximum: 25 **g/l** of VOC

**16. FURTHER INFORMATIONS**

Text of -R- phrases quoted in section 3 of the sheet.

R23/24/25	TOXIC BY INHALATION, IN CONTACT WITH SKIN AND IF SWALLOWED.
R50/53	VERY TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECT IN THE AQUATIC ENVIRONMENT.
R23/24	TOXIC BY INHALATION AND IN CONTACT WITH SKIN.
R34	CAUSES BURNS.
R43	MAY CAUSE SENSITIIZATION BY SKIN CONTACT.

**GENERAL BIBLIOGRAPHY**

1. Regulation 1999/45/CE and following amendments;
2. Regulation 67/548/CEE and following amendments and adjustments (technical adjustment XXVIII);
3. Regulation 91/155/CEE and following amendments;
4. The Merck Index. - 10th Edition;
5. Handling Chemical Safety;
6. Niosh - Registry of Toxic Effects of Chemical Substances;
7. INRS - Fiche Toxicologique (toxicological sheet);
8. Patty - Industrial Hygiene and Toxicology;
9. N.I. Sax-Dangerous properties of Industrial Materials-7, 1989 Edition;

**Note for users:**

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product. This document must not be regarded as a guarantee on any specific product property. The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Changes to previous review  
The following sections were modified:  
01 / 02 / 03 / 04 / 08 / 09 / 11/ 15/ 16