



# PRIMER ONE

## Fine white primer for interiors

**RIALTO PRIMER ONE** is a white hiding priming coat based on fine particle of polymer emulsions with high adhesion properties, fine aggregates, titanium dioxide and a broad spectrum anti-mould agents. Its adhesion and binding properties make it the ideal basecoat for application of acrylic paints, acrylic stucco and smooth plasters, particularly over smooth, flat substrates.

### PROPERTIES

- high adhesion capacity
- good water vapor permeability
- not harmful
- permanent fungicide
- good hiding power
- not flammable
- easy to use either by brush or roller
- specific gravity:  $1.55 \pm 0.05$  kg/l
- viscosity at quality control: non – Newtonian product
- average value  $> 12.500 \pm 1.000$  mPas
- percentage solids:  $64,00 \pm 2$  % by weight

### PURPOSES

**RIALTO PRIMER ONE** is suitable for the following applications:

- matte white basecoat for interior walls
- white priming coat for drywall, plasterboards particularly smooth and flat where **RIALTO FINISH** may be too rough for the desired smooth plaster effect
- bonding agent on dusty substrates like gypsum
- bonding agent highly compatible with acrylic paints and decorative acrylic stuccos for interiors
- anti-mould basecoat for application of anti-mould finishing paints in areas prone to growth of fungus

### WORKING INSTRUCTIONS

- clean surface and remove any loose material before applying **RIALTO PRIMER ONE**
- remove any mould prior to application of **RIALTO PRIMER ONE**
- before use, dilute **RIALTO PRIMER ONE** with 30% water
- mix it thoroughly to disperse homogenously the fine hiding particles of **RIALTO PRIMER ONE**
- apply **RIALTO PRIMER ONE** by brush or roller in one single coat, on highly absorbing surfaces a second coat might be necessary, wait at least 6 hours before applying next coat.
- clean brushes and any other utensils with water immediately after use
- store the product at a temperature above 5°C (41°F) and below 35°C (95°F)
- application of the desired final decoration, such as acrylic paints or acrylic stucco, can be done after 24 hours drying of **RIALTO PRIMER ONE**
- dispose of product with care
- dispose of waste through authorized waste disposal services

### COVERAGE

The average coverage of **RIALTO PRIMER ONE** is 8 – 12 sqm/l (120 – 180 sqm/15l pail, 1,300 – 1,900 sq.ft./15l pail) but may vary according to the absorption of the substrate and application method

### PACKAGING

**RIALTO PRIMER ONE** is available in 15 l and 4 l containers

For further help or information regarding the products in the **RIALTO** range contact your local dealer.

Every care has been taken to ensure that the information provided in this technical data sheet is accurate. **Harpo** is unable to guarantee results as it has no control over the conditions under which its products are applied.