



# PRIMER

## Penetrating and fixing colorless priming coat for interiors and exteriors

**RIALTO PRIMER** is based on an acrylic resin binder treated with selected additives in order to achieve particular penetration properties and improve adhesion.

### PROPERTIES

**RIALTO PRIMER** is marked by and stands out for the following characteristics:

- it is remarkably flexible
- it provides excellent adhesion
- it is permeable by water vapor
- it is non-toxic
- it is non-flammable
- specific gravity: 1.03 kg/l
- pH: 5.5 ± 0.5
- viscosity: 600 ± 100 mPas
- dry residue: 45 ± 1% by weight

### PURPOSES

**RIALTO PRIMER** is particularly suitable for:

- undercoats and for absorption control on interior and exterior surfaces
- binder for dusty gypsum plasterboard or gypsum walls
- anchoring surfaces such as polystyrene or polyester panels which become dusty owing to exposure to UV rays

### WORKING INSTRUCTIONS

- before applying **RIALTO PRIMER** remove any loose material, loose paint film by using a hard bristle brush or scraper; remove any traces of mould
- dilute with water according to whether **RIALTO PRIMER** is to be used on:
  - exterior plasters as a binder and fixing agent (**RIALTO PRIMER**/water ratio: 1:10)
  - interior plaster or gypsum surfaces (**RIALTO PRIMER**/water ratio: 1:8)
  - old washable paint, temper, tuff, bricks and artificial stone (**RIALTO PRIMER**/water ratio: 1:6)
- apply **RIALTO PRIMER** with brush, roller or spray
- should absorption of surface be particularly high, apply two coats at 3-4 hours intervals between coats. Do not create superficial films
- brushes and any other utensil must be cleaned with water immediately after use
- do not apply **RIALTO PRIMER** during rainy weather or on frozen surfaces
- allow at least 6 hours to dry before applying finishing products
- do not apply at air surface temperature below 5°C (41°F) or exceeding 35°C (95°F)
- store **RIALTO PRIMER** at temperatures above 5°C (41°F) and not exceeding 40°C (104°F)
- dispose of product with care
- dispose of waste through authorized waste disposal services

### COVERING CAPACITY

The spreading rate is calculated according to dilution and surface to which the product is applied.

The spreading rate ranges from 10 m<sup>2</sup>/l (400 sq.ft./gal) to a maximum of 50 m<sup>2</sup>/l (2,000 sq.ft./gal).

### PACKAGING

**RIALTO PRIMER** is available in 1 l, 5 l and 20 l containers.

For further help or information regarding the products in the **RIALTO** range contact your local dealer.

Every care has been taken to ensure that the information provided in this technical data sheet is accurate. **Harpo** is unable to guarantee results as it has no control over the conditions under which its products are applied.